

### FEATURES

- LOW Cost,High Quality
- Compact Size,Light Weight
- High Performance
- Wide Operation Temperature Range
- Octave and Multi-octave Bands

### APPLICATIONS

- Load isolation
- Module integration



### ELECTRICAL SPECIFICATIONS@25°C:

| Parameter       | Min   | Typical | Max   | Units |
|-----------------|-------|---------|-------|-------|
| Frequency Range | 10.95 |         | 14.75 | GHz   |
| Insertion Loss  |       |         | 0.5   | dB    |
| Isolation       | 20    |         |       | dB    |
| VSWR            |       |         | 1.25  | Ratio |
| Power Handling  |       |         | 10    | Watt  |

### ENVIRONMENTAL RATINGS:


| Parameter                          | Min   | Typical   | Max   | Units |
|------------------------------------|-------|-----------|-------|-------|
| Operating Temperature              | -40   |           | +70   | ℃     |
| Non-operating Temperature          | -40   |           | 85    | ℃     |
| Relative humidity (non-condensing) |       | 95        |       | %     |
| Altitude (MIL-STD-810F)            | 10000 |           | 30000 | Feet  |
| Shock / Vibration (MIL-STD-810F)   |       | Airbone   |       |       |
| ROHS                               |       | Compliant |       |       |

### MECHANICAL SPECIFICATIONS:

| Parameter            | Value    | Limits | Units     |
|----------------------|----------|--------|-----------|
| Dimensions(L*W*H)    | 15*19*13 | Max    | Milimeter |
| Weight               | 80       | Max    | gram      |
| RF Connectors Input  | SMA-F    |        |           |
| RF Connectors output | SMA-F    |        |           |
| Impedance            | 50       |        | Ohms      |

**Other frequency bands&specifications are also available**

### OUTLINE DRAWING(mm):



CC16