

FEATURES

- DC-40GHz, up to 50kW
- High Reliability, Repeatable Performance
- Anti-pulse and Anti-burnout
- Low IM3 Versions Available

APPLICATIONS

- Military & Space
- Radar&Electronic warfare
- Test Equipment

SPECIFICATIONS@25°C:

Part Number	Frequency Range (GHz)	VSWR	Power Handling (Watt.Average)	Power Handling (KW.Peak)	Connectr Type
MCT830H25KL	30KHz-800MHz	1.1-1.25	800		IF110 IF70 L36
MCT830H50KL	30KHz-800MHz	1.1-1.25	50KW		IF110
MCT010H05KL	DC-1	1.4	5000	100	L27 7/16 L52
MCT010H10KM	DC-1	1.0-1.45	10000	100	L26 L36 L52
MCT010H10KL	DC-1	1.4	1000	100	L27 7/16 L52
MCT020H01KA	DC-2	1.3	1000	50	N 7/16 L27
MCT020H01KH	DC-2	1.3	1000	50	N 7/16 L27
MCT020H01KL	DC-2	1.3	1000	50	N 7/16 L27
MCT020H01KM	DC-2	1.3	1000	50	N 7/16 L27
MCT020H02KA	DC-2	1.3	2000	50	N 7/16 L27
MCT020H02KH	DC-2	1.3	2000	50	N 7/16 L27
MCT020H02KL	DC-2	1.3	2000	50	N 7/16 L27
MCT020H02KM	DC-2	1.3	2000	50	N 7/16 L27
MCT020H03KL	DC-2	1.3	3000	50	L27 7/16 L36
MCT040H01KL	DC-4	1.2-1.5	1000	10	N 7/16 L27
MCT040H02KL	DC-4	1.2-1.75	2000	10	N 7/16 L27
MCT040H15KL	DC-4	1.2-1.75	1500	10	N 7/16 L27
MCT040H800L	DC-4	1.2-1.45	800	10	N 7/16
MCT040H800M	DC-4	1.2-1.45	800	10	N 7/16
MCT080H01KL	DC-8	1.15-1.55	1000	5	N
MCT080H01KM	DC-8	1.15-1.55	1000	5	N