



WIDE BAND MEDIUM POWER AMPLIFIER

MBM0618G3827

FEATURES

- Wide Bandwidth
- Low Power Consumption
- Low Noise Figure
- Miniature Sizes for drop-In Assembly
- Hermetically Sealed Package for Military Application

APPLICATIONS

- Microwave Radio & VSAT
- Military & Space
- Test Instrumentation
- Fiber Optics



ELECTRICAL SPECIFICATIONS@25°C:

Parameter	Min	Typical	Max	Units
Frequency Range	6		18	GHz
Small Signal Gain	38			dB
Small Signal Gain Flatness			±2	dB
Noise Figure			5.5	dB
Output Power 1dB compression	27			dBm
IP3				dBm
VSWR			2:1	Ratio
DC Power Supply		12		Volt
Current		100		mA

ENVIRONMENTAL RATINGS:

Parameter	Min	Typical	Max	Units
Max Input power			+20	dBm
Operating Temperature	-40		+85	°C
Non-operating Temperature	-55		+125	°C
Relative humidity (non-condensing)		95		%
Altitude (MIL-STD-810F)	10000		30000	feet
Shock / Vibration (MIL-STD-810F)		Airbone		

MECHANICAL SPECIFICATIONS:

Parameter	Value	Limits	Units
Dimensions	46.4*45*16		Milimeter
Weight	100		gram
RF Connectors Input	SMA-F		
RF Connectors output	SMA-F		
Impedance	50		Ohms


Note:miniature size,drop-in ,SMT and customized specification is also available

Meuro Microwave Corp. A#15F No.58 Shuxi Rd Jingcheng International Plaza,Chengdu, 610036 Tel: (028)8500 4482 Fax: (028)8500 4481
sales@meurorf.com www.meurorf.com



WIDE BAND MEDIUM POWER AMPLIFIER MBM0618G3827

OUTLINE DRAWING(mm):



BH8