



WIDE BAND DIGITAL CONTROL ATTENUATOR

MDC000130R30B5

FEATURES

- Whole Solid State, Mixture Integrated
- Low Power Consumption
- Excellent Flatness & Accuracy
- Miniature Sizes for drop-In available

APPLICATIONS

- Military & Space
- Radar & Electronic warfare
- Test Equipment



ELECTRICAL SPECIFICATIONS @ 25°C:

Parameter	Min	Typical	Max	Units
Frequency Range	0		13	GHz
Insertion Loss			3.2	dB
Mean attenuation Range	0		31.5	dB
Step Size			1	dB
Control bits		5		bits
Attenuation accuracy			±1.5	dB
Speed			45	ns
Flatness		±0.5		dB
VSWR			2:1	Ratio
DC Power +5V		50		mA
DC Power -5V		50		mA

ENVIRONMENTAL RATINGS:

Parameter	Min	Typical	Max	Units
Max Input Power			27	dBm
Operating Temperature	-40		+70	°C
Non-operating Temperature	-55		85	°C
Relative humidity (non-condensing)		95		%
Altitude (MIL-STD-810F)	10000		30000	feet
Shock / Vibration (MIL-STD-810F)		Airbone		
ROHS		Compliant		


MECHANICAL SPECIFICATIONS:

Parameter	Value	Limits	Units
Dimensions	30*18*10		Millimeter
Weight	100	type	gram
RF Connectors Input	SMA-F removable		
RF Connectors output	SMA-F removable		
Impedance	50		ohms



WIDE BAND DIGITAL CONTROL ATTENUATOR MDC000130R30B5

OUTLINE DRAWING(mm):



T4