

FEATURES

- DC-40GHz, up to 10kW
- Flatness Attenuation Value and Accuracy
- High Reliability, Repeatable Performance
- Anti-pulse and Anti-burnout
- Low IM3 Versions Available

APPLICATIONS

- Military & Space
- Radar&Electronic warfare
- Test Equipment



ELECTRICAL SPECIFICATIONS@25°C:


Frequency Range(GHz)	Attenuation Value & Accuracy (dB)					Max VSWR
	1-9	10	20	30	40	
DC-1	±0.4	±0.3	±±0.3	±0.3	±0.3	1.15
DC-2	±0.5	±0.4	±0.4	±0.5	±0.5	1.20
DC-3	±0.6	±0.5	±0.5	±0.6	±0.6	1.30
DC-4	±0.75	±0.75	±0.75	±0.75	±0.75	1.35

How to order: MFT040F060F40L-XX,if order 30dB attenuator part number will be MFT040F060F40L-30.XX:Atten Value.

MECHANICAL SPECIFICATIONS:

Parameter	Value	Limits	Units
Dimensions	130*80*60		Millimeter
Weight	510	type	gram
Operating Temperature	-55~+125		°C
Impedance	50		ohms

OUTLINE DRAWING(mm):



Note:

- 1.Average power:60W @ 25°C ,6W @ 125°C.
- 2.Peak power:10KW (5μs pulse width with 0.5% duty cycle)
- 3.Connector type: N, SMA, 7/16, TNC, BNC, please remark connector type. Standard is N-M input ,N-F output.
- 4.Customized special attenuation value & accuracy is also available.