



WIDE BAND LOW NOISE AMPLIFIER

MLB0102G3009

FEATURES

- Wide Bandwidth
- Low Power Consumption
- Low Noise Figure
- Miniature Sizes, Field Removable connector
- Compact/Rugged Thin-Film Construction

APPLICATIONS

- Microwave Radio & VSAT
- Military & Space
- Test Instrumentation
- Fiber Optics



ELECTRICAL SPECIFICATIONS@25°C:

Parameter	Min	Typical	Max	Units
Frequency Range	1.1		2.3	GHz
Small Signal Gain	30			dB
Small Signal Gain Flatness			±1.5	dB
Noise Figure			0.9	dB
Output Power 1dB compression			5	dBm
IP3				dBm
VSWR Input/output			2:1	Ratio
DC Power Supply		12		Volt
Current		120		mA

ENVIRONMENTAL RATINGS:

Parameter	Min	Typical	Max	Units
Max Input power			+20	dBm
Operating Temperature	-40		+85	°C
Non-operating Temperature	-55		+125	°C
Relative humidity (non-condensing)		95		%
Altitude (MIL-STD-810F)	10000		30000	feet
Shock / Vibration (MIL-STD-810F)		Airbone		

MECHANICAL SPECIFICATIONS:

Parameter	Value	Limits	Units
Dimensions	16.3*17.8*7.3	Max	Millimeter
Weight	50	Max	gram
RF Connectors Input	SMA-F		
RF Connectors output	SMA-M		
Impedance	50		ohms

Note:miniature size,drop-in ,SMT and customized specification is also available

[illegible]

Meuro Microwave Corp. A#15F No.58 Shuxi Rd Jingcheng International Plaza, Chengdu, 610036 Tel: (028)8500 4482 Fax: (028)8500 4481
sales@meurorf.com www.meurorf.com