



WIDE BAND LOW NOISE AMPLIFIER

MLB0218G2045

FEATURES

- Wide Bandwidth
- Low Power Consumption
- Low Noise Figure
- Miniature Sizes, Field Removable connector
- Compact/Rugged Thin-Film Construction

APPLICATIONS

- Microwave Radio & VSAT
- Military & Space
- Test Instrumentation
- Fiber Optics



ELECTRICAL SPECIFICATIONS@25°C:

Parameter	Min	Typical	Max	Units
Frequency Range	2		18	GHz
Small Signal Gain	20		27	dB
Small Signal Gain Flatness			±2	dB
Noise Figure			4.5	dB
Output Power 1dB compression	10			dBm
IP3				dBm
VSWR Input/output			2.2:1	Ratio
DC Power Supply		15		Volt
Current		120		mA

ENVIRONMENTAL RATINGS:


Parameter	Min	Typical	Max	Units
Max Input power			+20	dBm
Operating Temperature	-55		+85	°C
Non-operating Temperature	-55		+125	°C
Relative humidity (non-condensing)		95		%
Altitude (MIL-STD-810F)	10000		30000	feet
Shock / Vibration (MIL-STD-810F)		Airbone		

MECHANICAL SPECIFICATIONS:

Parameter	Value	Limits	Units
Dimensions	34.4*16.8*8.1	Max	Millimeter
Weight	50	Max	gram
RF Connectors Input	SMA-F		
RF Connectors output	SMA-F		
Impedance	50		ohms

Note:miniature size,drop-in ,SMT and customized specification is also available

OUTLINE DRAWING(mm):



BH2

TEST DATA:

Frequency range(GHZ)	GAN (dB.Min)	Gain Flatness $\pm$ (dB)	Noise Figure (dB.Max)	Output Power P-1(dB.Min)	Input VSWR Max	Output VSWR Max	DC Power Supply @+12V (mA)
2-18	23	± 1.0	4	11	1.78	1.8	130