



WIDE BAND LOW NOISE AMPLIFIER

MLB0812G3013

FEATURES

- Wide Bandwidth
- Low Power Consumption
- Low Noise Figure
- Miniature Sizes, Field Removable connector
- Compact/Rugged Thin-Film Construction

APPLICATIONS

- Microwave Radio & VSAT
- Military & Space
- Test Instrumentation
- Fiber Optics



ELECTRICAL SPECIFICATIONS@25°C:

Parameter	Min	Typical	Max	Units
Frequency Range	8		12	GHz
Small Signal Gain	30			dB
Small Signal Gain Flatness			±1.25	dB
Noise Figure			1.3	dB
Output Power 1dB compression	10			dBm
IP3				dBm
VSWR Input/output			2:1	Ratio
DC Power Supply		12		Volt
Current		180		mA

ENVIRONMENTAL RATINGS:

Parameter	Min	Typical	Max	Units
Max Input power			+20	dBm
Operating Temperature	-40		+85	°C
Non-operating Temperature	-55		+125	°C
Relative humidity (non-condensing)		95		%
Altitude (MIL-STD-810F)	10000		30000	feet
Shock / Vibration (MIL-STD-810F)		Airbone		

MECHANICAL SPECIFICATIONS:


Parameter	Value	Limits	Units
Dimensions	34.4*16.8*8.1	Max	Millimeter
Weight	50	Max	gram
RF Connectors Input	SMA-F		
RF Connectors output	SMA-F		
Impedance	50		ohms

Note:miniature size,drop-in ,SMT and customized specification is also available

WIDE BAND LOW NOISE AMPLIFIER

MLB0812G3013

OUTLINE DRAWING(mm):



BH2


TEST DATA:

Characteristic	Specification	Test Data
Part Number	MLB0812G3013	MLB0812G3013
Frequency Range	8-12GHz	8-12GHz
Small Signal Gain	30dB	32.48dB
Small Signal Gain Flatness	±1.25dB	±1.23dB
Noise Figure	1.3dB	1.3dB
Output Power 1dB compression	10dBm	11.8dBm
VSWR Input/output	2:1	1.95:1
DC Power Supply	12V	12V
Current	180mA	160mA



WIDE BAND LOW NOISE AMPLIFIER MLB0812G3013


TEST CURVE:



WIDE BAND LOW NOISE AMPLIFIER

MLB0812G3013

OUTLINE DRAWING(mm):



BH2

TEST DATA:

Characteristic	Specification	Test Data
Part Number	MLB0812G3013	MLB0812G3013
Frequency Range	8-12GHz	8-12GHz
Small Signal Gain	30dB	32.48dB
Small Signal Gain Flatness	±1.25dB	±1.23dB
Noise Figure	1.3dB	1.3dB
Output Power 1dB compression	10dBm	11.8dBm
VSWR Input/output	2:1	1.95:1
DC Power Supply	12V	12V
Current	180mA	160mA