

FEATURES

- Wide Bandwidth
- Low Insertion Loss
- Lower limiting threshold
- Miniature Sizes for drop-In Assembly
- Rugged/compact Thin Film Construction
- High power handling

**APPLICATIONS**

- Front End Protection for LNA's
- Power Leveling (Limiting)
- Receiver Protection

ELECTRICAL SPECIFICATIONS@25°C:

Parameter	Min	Typical	Max	Units
Frequency Range	1		2	GHz
insertion Loss			0.7	dB
VSWR Input/output			1.5:1	Ratio
Threshold		10		dBm
Spike leakage			12	dBm
input power 1% duty cycle peak			200	Watt
Pulse Width		1		us
Input power CW			2	Watt
Recovery Time		50		ns


ENVIRONMENTAL RATINGS:

Parameter	Min	Typical	Max	Units
Operating Temperature	-40		+85	°C
Non-operating Temperature	-55		125	°C
Relative humidity (non-condensing)		95		%
Altitude (MIL-STD-810F)	10000		30000	feet
Shock / Vibration (MIL-STD-810F)		Airbone		

MECHANICAL SPECIFICATIONS:

Parameter	Value	Limits	Units
Dimensions(L*W*H)	17.8*12.6*9.5	Max	Milimeter
Weight	50	Max	gram
RF Connectors Input	SMA-F		
RF Connectors output	SMA-F		
Impedance	50		Ohms

OUTLINE DRAWING(mm):



TEST DATA:

Temperature (°C)	Frequency range (GHz)	Insertion Loss (Max) $\leq 0.7\text{dB}$	Input VSWR (Max) ≤ 1.5	Output VSWR (Max) ≤ 1.5
25	1-2	0.33	1.13	1.1