



WAVEGUIDE HIGH POWER LIMITER MLT086094H015K

FEATURES

- High Power Handling
- Low Limiting Threshold
- Low Leakage Level
- Miniature Sizes

APPLICATIONS

- Front End Protection for LNA's
- Power Leveling (Limiting)
- Receiver Protection
- Radar&EW system



ELECTRICAL SPECIFICATIONS@25°C:

Parameter	Min	Typical	Max	Units
Frequency Range	8.6		9.4	GHz
Peak Power handling			1.5	KW
Overload Power handling			15	KW
Pulse Width			20	Us
duty Cycle			5	%
insertion Loss			1.0	dB
Flatness Leakage			50	mW
Spike Leakage			2	Watt
VSWR Input/Output			1.4	Ratio
recovery Time		1uSec @ 20uSec Pulse Width		

ENVIRONMENTAL RATINGS:

Parameter	Min	Typical	Max	Units
Operating temperature	-40		+75	°C
Non-operating Temperature	-55		125	°C
Relative humidity(non-condensing)	-95		98	%
Altitude (MIL-STD_810F)	10000		30000	feet
Shock/Vibration(MIL-Std_810F)		Airbone		
Pressurization	30			Psig

MECHANICAL SPECIFICATIONS:

Parameter	Value	Limits	Units
Dimensions	61*56*42	Max	Millimeter
Weight	300	Max	gram
RF Connectors Input	WR90		
RF Connectors output	WR90		



WAVEGUIDE HIGH POWER LIMITER MLT086094H015K

OUTLINE DRAWING(mm):

