



WAVEGUIDE HIGH POWER LIMITER MLT090096H02KK

FEATURES

- High Power Handling
- Low Limiting Threshold
- Low Leakage Level
- Miniature Sizes

APPLICATIONS

- Front End Protection for LNA's
- Power Leveling (Limiting)
- Receiver Protection
- Radar&EW system



ELECTRICAL SPECIFICATIONS@25°C:

Parameter	Min	Typical	Max	Units
Frequency Range	9		9.6	GHz
Peak Power handling			200	KW
Pulse Width			1	Us
duty Cycle			0.1	%
insertion Loss			1.2	dB
Flatness Leakage			30	mW
Spike Leakage			2	Watt
VSWR				Ratio
recovery Time			3	Us

Note:Type:TRD.

ENVIRONMENTAL RATINGS:

Parameter	Min	Typical	Max	Units
Operating temperature	-40		+75	°C
Non-operating Temperature	-55		125	°C
Relative humidity(non-condensing)	-95		98	%
Altitude (MIL-STD_810F)	10000		30000	feet
Shock/Vibration(MIL-Std_810F)		Airbone		
Pressurization	30			Psig

MECHANICAL SPECIFICATIONS:

Parameter	Value	Limits	Units
Dimensions	30.4*82/82.5*53	Max	Millimeter
Weight	300	Max	gram
RF Connectors Input	BJ-100		
RF Connectors output	BJ-100		



WAVEGUIDE HIGH POWER LIMITER

MLT090096H02KK

OUTLINE DRAWING(mm):

