



WAVEGUIDE HIGH POWER LIMITER MLT091096H4KW

FEATURES

- High Power Handling
- Low Limiting Threshold
- Low Leakage Level
- Miniature Sizes

APPLICATIONS

- Front End Protection for LNA's
- Power Leveling (Limiting)
- Receiver Protection
- Radar&EW system



ELECTRICAL SPECIFICATIONS@25°C:

Parameter	Min	Typical	Max	Units
Frequency Range	9.1		9.6	GHz
Power handling CW			3	KW
Average Power handling			40	Watt
insertion Loss			0.8	dB
Flatness Leakage			20	mW
Spike Leakage			100	Watt
VSWR Input/Output			1.4	Ratio
3dB recovery Time			1	Us

ENVIRONMENTAL RATINGS:

Parameter	Min	Typical	Max	Units
Operating temperature	-40		+75	°C
Non-operating Temperature	-55		125	°C
Relative humidity(non-condensing)	-95		98	%
Altitude (MIL-STD_810F)	10000		30000	feet
Shock/Vibration(MIL-Std_810F)		Airbone		
Pressurization	30			Psig


MECHANICAL SPECIFICATIONS:

Parameter	Value	Limits	Units
Dimensions	TBD	Max	Millimeter
Weight	800	Max	gram
RF Connectors Input	WR90		
RF Connectors output	WR90		



WAVEGUIDE HIGH POWER LIMITER MLT091096H4KW

OUTLINE DRAWING(mm):



WL1