



WAVEGUIDE HIGH POWER LIMITER MLT098088H02KK

FEATURES

- High Power Handling
- Low Limiting Threshold
- Low Leakage Level
- Miniature Sizes

APPLICATIONS

- Front End Protection for LNA's
- Power Leveling (Limiting)
- Receiver Protection
- Radar&EW system



ELECTRICAL SPECIFICATIONS@25°C:

Parameter	Min	Typical	Max	Units
Frequency Range	8.8		9.8	GHz
Peak Power handling			200	KW
Pulse Width			1	Us
duty Cycle			0.1	%
insertion Loss			0.8	dB
Flatness Leakage			300	mW
Spike Leakage			2	Watt
VSWR			1.7:1	Ratio
recovery Time			1.3	Us

Note:Type:PSTR.

ENVIRONMENTAL RATINGS:

Parameter	Min	Typical	Max	Units
Operating temperature	-40		+75	°C
Non-operating Temperature	-55		125	°C
Relative humidity(non-condensing)	-95		98	%
Altitude (MIL-STD_810F)	10000		30000	feet
Shock/Vibration(MIL-Std_810F)		Airbone		
Pressurization	30			Psig

MECHANICAL SPECIFICATIONS:

Parameter	Value	Limits	Units
Dimensions	26.5*80*47	Max	Millimeter
Weight	300	Max	gram
RF Connectors Input	TBD		
RF Connectors output	TBD		



WAVEGUIDE HIGH POWER LIMITER

MLT098088H02KK

OUTLINE DRAWING(mm):

