



NARROW BAND LOW NOISE AMPLIFIER

MNL048053G3407

FEATURES

- Wide Bandwidth
- Low Power Consumption
- Low Noise Figure
- Miniature Sizes for drop-In Assembly
- Hermetically Sealed Package for Military Application

APPLICATIONS

- Microwave Radio & VSAT
- Military & Space
- Test Instrumentation
- Fiber Optics



ELECTRICAL SPECIFICATIONS@25°C:

Parameter	Min	Typical	Max	Units
Frequency Range	4.85		5.35	GHz
Small Signal Gain	34			dB
Small Signal Gain Flatness			±0.5	dB
Noise Figure			0.7	dB
Output Power 1dB compression	10			dBm
IP3				dBm
VSWR Input/output			1.5:1	Ratio
DC Power Supply		12		Volt
Current		250		mA

ENVIRONMENTAL RATINGS:

Parameter	Min	Typical	Max	Units
Max Input power				dBm
Operating Temperature	-55		+85	°C
Non-operating Temperature	-55		125	°C
Relative humidity (non-condensing)		95		%
Altitude (MIL-STD-810F)	10.000		30000	feet
Shock / Vibration (MIL-STD-810F)		Airbone		

MECHANICAL SPECIFICATIONS:

Parameter	Value	Limits	Units
Dimensions	40.7*16.8*8.1	Max	Millimeter
Weight	50	Max	gram
RF Connectors Input	SMA-F		
RF Connectors output	SMA-F		
Impedance	50		ohms


Note:miniature size,drop-in ,SMT and customized specification is also available



NARROW BAND LOW NOISE AMPLIFIER

MNL048053G3407

OUTLINE DRAWING(mm):



BH3