



NARROW BAND LOW NOISE AMPLIFIER

MNL090095G3619

FEATURES

- Wide Bandwidth
- Low Power Consumption
- Low Noise Figure
- Miniature Sizes, Field Removable connector
- Compact/Rugged Thin-Film Construction

APPLICATIONS

- Microwave Radio & VSAT
- Military & Space
- Test Instrumentation
- Fiber Optics



ELECTRICAL SPECIFICATIONS@25°C:

Parameter	Min	Typical	Max	Units
Frequency Range	9.0		9.5	GHz
Small Signal Gain	36			dB
Small Signal Gain Flatness			±0.75	dB
Noise Figure			1.9	dB
Output Power 1dB compression	12			dBm
IP3				dBm
VSWR Input/output			2:1	Ratio
DC Power Supply		12		Volt
Current		150		mA


ENVIRONMENTAL RATINGS:

Parameter	Min	Typical	Max	Units
Max Input power			+20	dBm
Operating Temperature	-40		+85	°C
Non-operating Temperature	-55		+125	°C
Relative humidity (non-condensing)		95		%
Altitude (MIL-STD-810F)	10000		30000	feet
Shock / Vibration (MIL-STD-810F)		Airbone		

MECHANICAL SPECIFICATIONS:

Parameter	Value	Limits	Units
Dimensions	46.9*16.8*8.1	Max	Millimeter
Weight	50	Max	gram
RF Connectors Input	SMA-F		
RF Connectors output	SMA-F		
Impedance	50		ohms

Note:miniature size,drop-in ,SMT and customized specification is also available

OUTLINE DRAWING(mm):**BH3****TEST DATA:**

characteristic	specification	test data
Part number	MNL090095G3619	MNL090095G3619
S/N		1
Frequency range	9-9.5GHz	9-9.5GHz
Small Signal Gain(min)	36dB	36.1dB
Small Signal Gain Flatness(max)	±0.75	±0.15
Noise Figure(max)	1.9dB	1.9dB
P1dB(min)	12dBm	15dBm
VSWR Input/output(max)	2:01	1.34/1.52
DC Power Supply	12v	12v
Current(typ)	150mA	180mA



NARROW BAND LOW NOISE AMPLIFIER

MNL090095G3619

