



NARROW BAND MEDIUM POWER AMPLIFIER

MNM023027G3530

FEATURES

- Wide Bandwidth
- Low Power Consumption
- Low Noise Figure
- Miniature Sizes for drop-In Assembly
- Hermetically Sealed Package for Military Application

APPLICATIONS

- Microwave Radio & VSAT
- Military & Space
- Test Instrumentation
- Fiber Optics



ELECTRICAL SPECIFICATIONS@25°C:

Parameter	Min	Typical	Max	Units
Frequency Range	2.3		2.7	GHz
Small Signal Gain	35			dB
Small Signal Gain Flatness			±1	dB
Noise Figure			6	dB
Output Power 1dB compression	30			dBm
Input VSWR			1.6:1	Ratio
Output VSWR			1.8 :1	Ratio
DC Power Supply		12		Volt
Current		850		mA

ENVIRONMENTAL RATINGS:

Parameter	Min	Typical	Max	Units
Max Input power			+20	dBm
Operating Temperature	-40		+85	°C
Non-operating Temperature	-55		+125	°C
Relative humidity (non-condensing)		95		%
Altitude (MIL-STD-810F)	10000		30000	feet
Shock / Vibration (MIL-STD-810F)		Airbone		

MECHANICAL SPECIFICATIONS:


Parameter	Value	Limits	Units
Dimensions	57.4*29.5*17	Max	Millimeter
Weight	50	Max	gram
RF Connectors Input	SMA-F		
RF Connectors output	SMA-F		
Impedance	50		ohms



NARROW BAND MEDIUM POWER AMPLIFIER

MNM023027G3530

OUTLINE DRAWING(mm):



DH6