



2-WAY WIDE BAND POWER DIVIDER MPD020080S2L

FEATURE

- Operating Frequency:0.5~18GHz
- Stable Performance and High Reliability
- High Isolation
- Low Insertion Loss
- Small Phase&Amplitude Errors
- Operating Temperature:-55~+85°C



APPLICATIONS

- Communication system
- Radar&Warfare system
- Test Equipment

ELECTRICAL SPECIFICATIONS@25°C:

Parameter	Min	Typical	Max	Units
Frequency Range	2		8	GHz
Isolation	20			dB
Insertion Loss			0.5	dB
VSWR Input			1.25	Ratio
VSWR Output			1.2	Ratio
Phase Balance			3	degree
Amplitude Balance			0.2	dB
Power Average			20	watt


ENVIRONMENTAL RATINGS:

Parameter	Min	Typical	Max	Units
Operating Temperature	-40		+85	°C
Non-operating Temperature	-55		125	°C
Relative humidity (non-condensing)		95		%
Altitude (MIL-STD-810F)	10000		30000	feet
Shock / Vibration (MIL-STD-810F)		Airbone		

MECHANICAL SPECIFICATIONS:

Parameter	Value	Limits	Units
Dimensions	28*28*10	Max	Millimeter
Weight	50	Max	gram
RF Connectors Input	SMA-F		
RF Connectors output	SMA-F		
Impedance	50		ohms

OUTLINE DRAWING(mm):



TEST DATA:

