



3-WAY WIDE BAND POWER DIVIDER

MPD080120S3M

FEATURE

- Operating Frequency:0.5~18GHz
- Stable Performance and High Reliability
- High Isolation
- Low Insertion Loss
- Small Phase&Amplitude Errors
- Operating Temperature:-55~+85°C

APPLICATIONS

- Communication system
- Radar&Warfare system
- Test Equipment



ELECTRICAL SPECIFICATIONS@25°C:

Parameter	Min	Typical	Max	Units
Frequency Range	8		12	GHz
Isolation	15			dB
Insertion Loss			1.0	dB
VSWR			1.5	Ratio
Phase Balance			±5	degree
Amplitude Balance			±0.5	dB
Power Handling(Forward)			10	watt
Power Handling(Reversed)			1	watt

ENVIRONMENTAL RATINGS:

Parameter	Min	Typical	Max	Units
Operating Temperature	-55		+85	°C
Non-operating Temperature	-55		125	°C
Relative humidity (non-condensing)		90		%
Altitude (MIL-STD-810F)	10000		30000	feet
Shock / Vibration (MIL-STD-810F)		Airbone		


MECHANICAL SPECIFICATIONS:

Parameter	Value	Limits	Units
Dimensions	96*56*10	Max	Millimeter
Weight	50	Max	gram
RF Connectors Input	SMA-F		
RF Connectors output	SMA-F		
Impedance	50		ohms



3-WAY WIDE BAND POWER DIVIDER MPD080120S3M

OUTLINE DRAWING(mm):



3D2