

FEATURES

- Wide Bandwidth
- Low Power Consumption
- Low Noise Figure
- Miniature Sizes for drop-In Assembly
- Rugged/compact Thin Film Construction

APPLICATIONS

- Microwave Radio & VSAT
- Military & Space
- Test Instrumentation
- Fiber Optics



ELECTRICAL SPECIFICATIONS@25°C:

Parameter	Min	Typical	Max	Units
Frequency Range	2		6	GHz
Input power Range	-30		+10	dBm
Noise Figure			5.0	dB
Saturated Power output	17		22	dBm
output Power Flatness			±1.8	dB
harmonic output		-10		dBc
VSWR Input/output			2:1	Ratio
Pulse response Overshoot			0.5	dB
Pulse response Recovery time		50		ns
Pulse response Settling time		50		ns
Pulse response Rise time		20		ns
DC Power Supply		12		Volt
Current		300		mA

ENVIRONMENTAL RATINGS:

Parameter	Min	Typical	Max	Units
Max Input power				dBm
Operating Temperature	-40		+85	°C
Non-operating Temperature	-55		125	°C
Relative humidity (non-condensing)		95		%
Altitude (MIL-STD-810F)	10000		30000	feet
Shock / Vibration (MIL-STD-810F)		Airbone		

Parameter	Valus	Limits	Units
Dimensions		Max	Millimeter
Weight	50	Max	gram
RF Connectors Input			
RF Connectors output	SMA-F		
Impedance			ohms

Technical drawing of the DH4 module showing front and top views with dimensions.

Front View Dimensions:

- Input: 9.2
- Earthing: 9.2
- Module Width: 17
- Module Height: 29.5
- Internal Feature Height: 14

Top View Dimensions:

- Module Length: 44.7
- Module Width: 17
- RF Input Port (RFin): 32
- RF Output Port (RFout): 6.6
- Grounding Points (GND +12V): 4-Φ2.5 Deep6.5

Meuro Microwave Corp. A#15F No.58 Shuxi Rd Jingcheng International Plaza, Chengdu, 610036 Tel: (028)8500 4482 Fax: (028)8500 4481
sales@meurorf.com www.meurorf.com