

FEATURE:

- Solid State,Mixture Integrated
- High Speed,Low Loss,High Isolation
- Field Removable SMA(F) Connector
- Integrated with Driver

APPLICATION:

- Test equipment
- Radar&Warfare system
- Communication system



SPECIFICATIONS@25°C:

Part Number	Frequency Range (GHz)	Insertion Loss (dB.Typ)	Isolation (dB.Min)	VSWR (Max)	Power Handling (Watt.Max)	Switching Time (ns.Max)	Current@ +/-5VDC (mA.Typ)	Case Type
SPST001005N6	0.1-0.5	1.1	60	1.5	1	50	30/20	SW1
SPST001005N8	0.1-0.5	1.1	80	1.5	1	50	30/20	SW1
SPST005010N6	0.5-1	0.8	60	1.5	1	50	30/20	SW1
SPST005010N8	0.5-1	1.1	80	1.5	1	50	30/20	SW1
SPST005180N6	0.5-18	2.1	60	2.2	1	50	30/20	SW1
SPST005180N8	0.5-18	2.5	80	2.2	1	50	30/20	SW1
SPST010020N6	1-2	0.7	60	1.5	1	50	30/20	SW1
SPST010020N8	1-2	1.2	80	1.5	1	50	30/20	SW1
SPST020040N6	2-4	0.9	60	1.5	1	50	30/20	SW1
SPST020040N8	2-4	1.3	80	1.5	1	50	30/20	SW1
SPST040080N6	4-8	1.2	60	1.7	1	50	30/20	SW1
SPST040080N8	4-8	1.4	80	1.7	1	50	30/20	SW1
SPST080120N6	8-12	1.5	60	1.7	1	50	30/20	SW1
SPST080120N8	8-12	1.9	80	1.7	1	50	30/20	SW1
SPST120180N8	12-18	2.5	80	2	1	50	30/20	SW1
SPST120180N6	12-18	2.1	60	2	1	50	30/20	SW1
SPST340360N6	34-36	5.5	60	2.2	/	/	30/20	SW9

