


FEATURE:

- Solid State,Mixture Integrated
- High Speed,Low Loss,High Isolation
- Field Removable SMA(F) Connector
- Integrated with Driver

APPLICATION:

- Test equipment
- Radar&Warfare system
- Communication system

**ELECTRICAL SPECIFICATIONS@25°C:**

Parameter	Min	Typical	Max	Units
Frequency Range	0.1		0.5	GHz
Insertion Loss		2.4		dB
Isolation	60			dB
VSWR			1.5	Ratio
Input Power			0.2	watt
Switching Time			50	ns
DC Power supply +5V		360		mA
DC Power supply -5V		240		mA

ENVIRONMENTAL RATINGS:

Parameter	Min	Typical	Max	Units
Operating Temperature	-40		+85	°C
Non-operating Temperature	-55		125	°C
Relative humidity (non-condensing)		95		%
Altitude (MIL-STD-810F)	10000		30000	feet
Shock / Vibration (MIL-STD-810F)		Airbone		

MECHANICAL SPECIFICATIONS:


Parameter	Value	Limits	Units
Dimensions	131*45.5*15	Max	Millimeter
Weight	200	Max	gram
RF Connectors Input	SMA-F		
RF Connectors output	SMA-F		
Impedance	50		ohms

TTL CONTROL LOGIC

TTL 0 (low) (0 to 0.8 V) :Loss

TTL 1 (high) (2.4 to 4.7 V) : Isolation

OUTLINE DRAWING(mm):



12W1