

FEATURE:

- Solid State,Mixture Integrated
- High Speed,Low Loss,High Isolation Integral with Driver
- Field Removable SMA(F) Connector
- Operating Temperature:-55~+85°C
- Contorl:TTL"0"Loss,TTL"1"Isolation

APPLICATION:

- Test equipment
- Radar&Warfare system
- Communication system



ELECTRICAL SPECIFICATIONS@25°C:

Parameter	Min	Typical	Max	Units
Frequency Range	2.7		3	GHz
Insertion Loss		0.6	0.8	dB
Isolation	30			dB
VSWR			1.4:1	Ratio
Response time			2	uS
Power handling (Peak)			300	watt
Duty Cycle		10		%
DC Power supply +5V		300		mA
DC Power supply -28V		50		mA

Note:Pulse width 100 micro second.

ENVIRONMENTAL RATINGS:

Parameter	Min	Typical	Max	Units
Operating Temperature	-40		+55	°C
Non-operating Temperature	-55		+85	°C
Relative humidity (non-condensing)		95		%
Altitude (MIL-STD-810F)	10000		30000	feet
Shock / Vibration (MIL-STD-810F)		Airbone		

MECHANICAL SPECIFICATIONS:

Parameter	Value	Limits	Units
Dimensions	TBD	Max	Millimeter
Weight	TBD	Max	gram
RF Connectors Input	N-F		
RF Connectors output	N-F		
Impedance	50		ohms


DC Power can be based on user's spec

TTL CONTROL LOGIC

TTL 0 (low) (0 to 0.8 V) :J0-J1

TTL 1 (high) (2.4 to 4.7 V) :J0-J2

OUTLINE DRAWING(mm):



TBD