

FEATURE:

- Solid State,Mixture Integrated
- High Speed,Low Loss,High Isolation Integral with Driver
- Field Removable SMA(F) Connector
- Operating Temperature:-55~+85°C
- Contorl:TTL“0”Loss,TTL“1”Isolation

APPLICATION:

- Test equipment
- Radar&Warfare system
- Communication system



ELECTRICAL SPECIFICATIONS@25°C:

Parameter	Min	Typical	Max	Units
Frequency Range	4.4		5	GHz
Insertion Loss			1	dB
Isolation	40			dB
VSWR			1.5:1	Ratio
Switching Times			2	uSec
Power handling average			40	watt
DC Power supply +5V		200		mA
DC Power supply -24V		50		mA

ENVIRONMENTAL RATINGS:

Parameter	Min	Typical	Max	Units
Operating Temperature	-40		+70	°C
Non-operating Temperature	-55		125	°C
Relative humidity (non-condensing)		95		%
Altitude (MIL-STD-810F)			15000	feet
Shock / Vibration (MIL-STD-810F)		Airbone		

MECHANICAL SPECIFICATIONS:


Parameter	Value	Limits	Units
Dimensions	50*30*19	Max	Millimeter
Weight	100	Max	gram
RF Connectors Input	SMA-F		
RF Connectors output	SMA-F		
Impedance	50		ohms

TTL CONTROL LOGIC

TTL 0 (low) (0 to 0.8 V) :J0-J1

TTL 1 (high) (2.4 to 4.7 V) :J0-J2

OUTLINE DRAWING(mm):



DW4