

### FEATURES

- LOW Cost,High Quality
- Compact Size,Light Weight
- High Performance
- Wide Operation Temperature Range
- Octave and Multi-octave Bands

### APPLICATIONS

- Load isolation
- Module integration



### ELECTRICAL SPECIFICATIONS@25°C:

| Parameter               | Min  | Typical | Max | Units |
|-------------------------|------|---------|-----|-------|
| Frequency Range         | 26.3 |         | 40  | GHz   |
| Band Width              |      | 1000    |     | MHz   |
| Insertion Loss          |      |         | 0.3 | dB    |
| Isolation               | 23   |         |     | dB    |
| VSWR                    |      |         | 1.2 | Ratio |
| Power Handling(average) |      |         | 30  | Watt  |

### ENVIRONMENTAL RATINGS:


| Parameter                          | Min   | Typical   | Max   | Units |
|------------------------------------|-------|-----------|-------|-------|
| Operating Temperature              | -40   |           | +80   | ℃     |
| Non-operating Temperature          | -40   |           | 85    | ℃     |
| Relative humidity (non-condensing) |       | 95        |       | %     |
| Altitude (MIL-STD-810F)            | 10000 |           | 30000 | Feet  |
| Shock / Vibration (MIL-STD-810F)   |       | Airbone   |       |       |
| ROHS                               |       | Compliant |       |       |

### MECHANICAL SPECIFICATIONS:

| Parameter            | Value      | Limits | Units     |
|----------------------|------------|--------|-----------|
| Dimensions(L*W*H)    | 21*24*19.1 | Max    | Milimeter |
| Weight               | 100        | Max    | gram      |
| RF Connectors Input  | SMA-F      |        |           |
| RF Connectors output | SMA-F      |        |           |
| Impedance            | 50         |        | Ohms      |


Other frequency bands&specifications are also available

### OUTLINE DRAWING(mm):



WR09

### HOW TO ORDER



Example: To order a 26.3-27.3GHz Circulator and specify WIR263400B-26.3-27.3