

FEATURES

- LOW Cost,High Quality
- Compact Size,Light Weight
- High Performance
- Wide Operation Temperature Range
- Octave and Multi-octave Bands

APPLICATIONS

- Load isolation
- Module integration



ELECTRICAL SPECIFICATIONS@25°C:

Parameter	Min	Typical	Max	Units
Frequency Range	26.5		40	GHz
Band Width		full		MHz
Insertion Loss			0.6	dB
Isolation	17			dB
VSWR			1.3:1	Ratio
Power Handling(FWD)			7.5	Watt

ENVIRONMENTAL RATINGS:


Parameter	Min	Typical	Max	Units
Operating Temperature	-20		+60	℃
Non-operating Temperature	-40		+85	℃
Relative humidity (non-condensing)		95		%
Altitude (MIL-STD-810F)	10000		30000	Feet
Shock / Vibration (MIL-STD-810F)		Airbone		
ROHS		Compliant		

MECHANICAL SPECIFICATIONS:

Parameter	Value	Limits	Units
Dimensions(L*W*H)	21*24*22.1	Max	Milimeter
Weight	30	Max	gram
RF Connectors Input	WR28		
RF Connectors output	WR28		
Impedance			Ohms

Other frequency bands&specifications are also available

OUTLINE DRAWING(mm):



WR28