

FEATURES

- LOW Cost,High Quality
- Compact Size,Light Weight
- High Performance
- Wide Operation Temperature Range
- Octave and Multi-octave Bands

APPLICATIONS

- Load isolation
- Module integration



ELECTRICAL SPECIFICATIONS@25°C:

Parameter	Min	Typical	Max	Units
Frequency Range	39.2		59.6	GHz
Band Width		1000		MHz
Insertion Loss			0.6	dB
Isolation	23			dB
VSWR			1.2	Ratio
Power Handling(average)			30	Watt

ENVIRONMENTAL RATINGS:


Parameter	Min	Typical	Max	Units
Operating Temperature	-40		+80	℃
Non-operating Temperature	-40		85	℃
Relative humidity (non-condensing)		95		%
Altitude (MIL-STD-810F)	10000		30000	Feet
Shock / Vibration (MIL-STD-810F)		Airbone		
ROHS		Compliant		

MECHANICAL SPECIFICATIONS:

Parameter	Value	Limits	Units
Dimensions(L*W*H)	10*24.5*19.1	Max	Milimeter
Weight	100	Max	gram
RF Connectors Input	WR18		
RF Connectors output	WR18		
Impedance	50		Ohms

Other frequency bands&specifications are also available

OUTLINE DRAWING(mm):



WN01

HOW TO ORDER

WIR392596A-xx-xx

Low End Frequency(MHz) High End Frequency(MHz)

Example: To order a 49600-50600MHz Circulator and specify WIR392596A-49600-50600