

FEATURES

- LOW Cost,High Quality
- Compact Size,Light Weight
- High Performance
- Wide Operation Temperature Range
- Octave and Multi-octave Bands

APPLICATIONS

- Load isolation
- Module integration



ELECTRICAL SPECIFICATIONS@25°C:

Parameter	Min	Typical	Max	Units
Frequency Range	94		94.1	GHz
Band Width		100		MHz
Insertion Loss			1	dB
Isolation	20			dB
VSWR			1.3	Ratio
Power Handling(Average)			30	Watt
Power Handling(Peak)			1.5	KW

ENVIRONMENTAL RATINGS:

Parameter	Min	Typical	Max	Units
Operating Temperature	-40		+80	℃
Non-operating Temperature	-40		85	℃
Relative humidity (non-condensing)		95		%
Altitude (MIL-STD-810F)	10000		30000	Feet
Shock / Vibration (MIL-STD-810F)		Airbone		
ROHS		Compliant		

MECHANICAL SPECIFICATIONS:

Parameter	Value	Limits	Units
Dimensions(L*W*H)	19.1*19.1*10	Max	Milimeter
Weight	100	Max	gram
RF Connectors Input	WR10		
RF Connectors output	WR10		
Impedance	50		Ohms

Other frequency bands&specifications are also available

OUTLINE DRAWING(mm):

